

D5 智慧锅炉



▫ 加热管, 特氟龙涂层, 365天防垢



▫ 蒸汽二次加热, 冬季使用更干燥

杰克锅炉 (Jack)

10分钟上汽, 加热管1年免维护,
集成二次加热蒸汽更干燥



其他锅炉 (other)

20分钟上汽, 加热管半年一换,
冬季熨烫湿度高

技术参数

机型	功率 (KW)	额定工作压力 (mpa)	额定蒸汽量 (kg/h)	饱和蒸汽温度 (°C)	电压	外型尺寸 (mm)	进水口口径	蒸汽口口径
U5-6/9M-DZ	6/9可调	0.8	8/12	174.1	220/380	640*360*720	Dn15	Dn15
U5-12M-DZ	12	0.8	16	174.1	220/380	640*360*720	Dn15	Dn15
U5-18M-DZ	18	0.8	24	174.1	220/380	640*360*720	Dn15	Dn15
U5-24M-DZ	24	0.8	32	174.1	380	640*360*720	Dn15	Dn15

D5 Smart boiler



👍 Heating tube, Teflon coating, 365 days anti-scaling



👍 Steam secondary heating, drier in winter

(Jack)

10 minutes SAIC, 1 year warranty for heating tube, integrated secondary heating steam for drier steam



(other)

SAIC in 20 minutes, the heating tube is changed every six months, and the ironing humidity is high in winter

Specification

Mode	power (KW)	rated working pressure (mpa)	Rated steam volume (kg/h)	saturated steam temperature (°C)	voltage	exterior size (mm)	Inlet diameter	Steam port diameter
U5-6/9M-DZ	6/9Adjustable	0.8	8/12	174.1	220/380	640*360*720	Dn15	Dn15
U5-12M-DZ	12	0.8	16	174.1	220/380	640*360*720	Dn15	Dn15
U5-18M-DZ	18	0.8	24	174.1	220/380	640*360*720	Dn15	Dn15
U5-24M-DZ	24	0.8	32	174.1	380	640*360*720	Dn15	Dn15